



PERFORMANCE LUBRICATION

PRODUCT INFORMATION

GLOBAL COMPLEX LT 2

Multifunctional grease for all kinds of uses

DESCRIPTION

Mineral-based and lithium complex soap grease with EP (Extreme Pressure) additives.

PERFORMANCE

STANDARDS: ISO – L – XBGE B 2

Especially recommended for the lubrication of:

- Bearings subject to high mechanical stress, high temperatures and the presence of water, as in granulators, automobiles, agricultural machinery and public works.
- Bearings for fans, ovens and dryers in the textile, wood, plastics and food industries.
- Bearings of grilles and steam-heated drying cylinders.

Its high drip point allows it to work at high temperatures.

High mechanical stability, maintaining its consistency, structure and adherence even under high-stress operating conditions, or in aggressive environments such as humidity and steam.

Good load-bearing capacity.

High protection against metal part corrosion.

High resistance to water.

CONDITIONS OF USE

Maintenance interval as recommended by each manufacturer and adapted to its own use.

TECHNICAL FEATURES

APPEARANCE:	Blue	CONSISTENCY:	NLGI 2
THICKENER:	Complex lithium	DRIP POINT:	260°C / 500 F
PENETRATION AT 60 cycles:	295	4-BALL TEST:	315 Kg
PENETRATION AT 10⁴ cycles:	325		

Rev.11/23



www.globalracingoil.com

Compañía General de Lubricantes, S.A. reserves the right to modify the general characteristics that appear in this document, until the customer places his order, subject to our general conditions of sale and guarantee.

